




Description

DME PROLINK's range of Category 6 Copper Patch Leads are designed for optimal performance and manageability. Our Patch Leads are designed to offer a slim profile specifically for today's high-density environments. Snag-less plug design makes these Patch Cords an excellent choice in environments where moves, adds and changes (MAC's) are frequent.

Features & Benefits

- Meets all requirements specified in ANSI/TIA-568-C.2
- Low Smoke Zero Halogen
- Connector wiring T568B wire scheme.
- Fully interoperable and backwards compatible
- UL Listed
- 25 Years System Warranty



TRANSMISSION PERFORMANCE

Near End Cross Talk	Meet all Requirements Specified in ANSI/TIA-568-C.2
Return Loss	Meet all Requirements Specified in ANSI/TIA-568-C.2

ELECTRICAL

Continuity	Change in Resistance <60 mili-Ohms, 10VDC
Dielectric Withstanding Voltage	1000 Volts, RMS, 60Hz, 1Min.

MECHANICAL

Plug

Assembly	Compatible with FCC Part 68 Subpart F
Housing	UL Listed 94V-0 Flame-Retardant PC (Polycarbonate)
IDC Blades	Phosphor Bronze. Contact area of blades is plated with 50 micro- inches of hard gold over 100 micro-inches of Nickel

Cordage

Jacket Dimension	Diameter <0.25 inches
Construction	CAT6 UTP 24 AWG 7 stranded 4-Pair Copper wire conductor. High Density Polyethylene Insulation Material. FR-PE Low Smoke Zero Halogen Jacket.

PHYSICAL

Plug Assembly	Polycarbonate, 94V-0, the contact Area of blades is plated with 50 micro- inches of hard gold over 100 micro-inches of Nickel
CAT6 Patch Cable	FR-PE Low Smoke Zero Halogen Jacket
Strain Relief	BASF TPU Low Smoke Zero Halogen

Part Number

D0225-UN1LSGY	Copper Patch Lead, CAT6, Unshielded, 1m, LSZH, Grey
D0224-UN2LSGY	Copper Patch Lead, CAT6, Unshielded, 2m, LSZH, Grey
D0224-UN3LSGY	Copper Patch Lead, CAT6, Unshielded, 3m, LSZH, Grey
D0225-UN5LSGY	Copper Patch Lead, CAT6, Unshielded, 5m, LSZH, Grey
D022x-UN10LSGY	Copper Patch Lead, CAT6, Unshielded, 10m, LSZH, Grey
D022x-UN20LSGY	Copper Patch Lead, CAT6, Unshielded, 20m, LSZH, Grey

Web Site: www.dmeprolink.com

Corporate Head Office: 3135 - 6900 Graybar Road, Richmond, BC V6W 0A5, Canada •
Phone: +1(604)276-9913 Fax: +1(604)276-9915. For a listing of all ECS Global Wire &
Cable's Sales Office locations, please refer to our web site.

Middle East Head Quarters: Jebel Ali Free Zone (South), Dubai, United Arab Emirates •
Phone: +971 (4) 811 8000 Fax: +971 (4) 8809360. Enquires to
datacomm@ecsglobalwire.com.

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ECS Global Wire & Cable reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting ECS Global Wire & Cable's Regional Head Office in the UAE.

June 2016 Original © 2016 ECS Global Wire & Cable. All Rights Reserved

