



## Description

DME PROLINK provides a Fiber Optic coupling adapter family to support interconnection. DME PROLINK adapters are available in a wide range of hybrid adapter styles to fit almost any application or panel. DME PROLINK quality personals ensures product reliability through rigorous qualification testing to assure cable performance and durability in adverse field environments. Excellent quality control is achieved through intense in-house quality check and stringent audit acceptance by ISO 9001.

## Features & Benefits

- Excellent Changeability and Directivity
- High quality Ceramic sleeves for high precision alignment
- Accurate mounting dimensions
- Complies with IEC 61754-4
- 25 Years System Warranty

## ETISALAT PRODUCT APPROVAL

EPA No: 780168-7  
 The Item: SC/APC Adapter  
 Supplied by M/s. ECS  
 Is provisionally approved for use in buildings intended to connect to Etisalat FTTH Network. Etisalat do not undertake any responsibility towards any damage or hazard caused due to the use of this product.  
 Approved valid till 15 May 2018  
 Authorized signatory (Signature)  
 Designation Single mode SD/DSH Date 15.5.17

## Technical Characteristics of Adapter

Fiber Type	Single mode
Adapter Type	SC
Insertion Loss (dB)	≤ 0.20
Repeatability (dB)	≤ 0.20
Interchangeability (dB)	≤ 0.20
Operating Temperature Range	-25°C to +70°C
Storage Temperature Range	-25°C to +70°C
Durability	> 500 times
Standard	IEC 601754-4

## Part Number

**D162x-SCASMS**

**Fiber Optic Coupling Adapter, SC/APC, Single mode, Simplex**