



Description

DME PROLINK's Fiber Optic Outlet is installed inside the customer's premises to provide fiber termination points and housing for optical adapters, FICs and Pigtailed.

The FOO is used as an interface/interconnection point between the customer's in-building fiber optic cabling system and the ONT (Optical Network Terminal equipment) patch cord.

DME PROLINK's FOO supports termination, splicing & storage functions for Customer Premises fiber optic cable systems. The FOO is simple in design yet offers sufficient work space and fiber management – the box is engineered with all fiber routing supporting the minimum bend radius philosophy to ensure signal integrity.

Features & Benefits

- Compact size takes up less wall space for installation
- Inner slack storage area ensures minimum bend radius compliance
- Simple and easy installation
- Inner tray available to house splice sleeves
- Accepts standard SC and LC Adapters
- Comes in both Loaded and Unloaded options
- Mounting screws, Fischer, Cable Ties provided.
- Complies with IEC 61754-4
- 25 Years System Warranty

ETISALAT PRODUCT APPROVAL	
EPA No:	780168-9
The item:	FO outlet
Supplied by M/s.	ECS
Is provisionally approved for use in buildings intended to connect to Etisalat FTTH Network. Etisalat do not undertake any responsibility towards any damage or hazard caused due to the use of this product.	
Approved valid till	15 May 2018
Authorized signatory	[Signature]
Designation	SD/OSHT
Date	16/5/18