



ETISAIAT PRODUCT APPROVAL

EPA No: 782168-4

The Item: SC/APC patch panel

Supplied by M/s. ECS

Is provisionally approved for use in buildings intended to connect to Etisalat FTTH Network. Etisalat do not undertake any responsibility towards any damage or hazard caused due to the use of this product.

Approved valid till 15 May 2018

Authorized signatory [Signature]

Designation for CD/DSH Date _____

Description

DME PROLINK provides 19" Rack-mountable Fiber Optic Patch Panel for splicing and/or termination of optical fibers in an indoor environment. Also, loaded type available with Multimode or Single-mode pigtails, splice accessories and adapters. The solution provides an optical channel that is guaranteed to be compliant with the ISO 11801 International Standard for Structured Cabling. DME PROLINK quality personals ensures product reliability through rigorous qualification testing to assure cable performance and durability in adverse field environments. Excellent quality control is achieved through intense in-house quality check and stringent audit acceptance by ISO 9001.

Features & Benefits

- 19" Rack-mountable; 1RU
- Easy to install.
- Comes Unloaded (Capacity 24 Ports)
- With Plastic Sliding Rail- Sliding Out Design
- Cable Fixing and Grounding Devices installed within Patch Panel
- The body made of cold-rolled steel. The steel plate thickness is 1.5mm, molded by numerical controlling. Surface treated with static plastic spray.
- Internal cable management
- Accommodates Splicing and/or Direct Termination
- Complies with IEC 60068
- Accepts DME PROLINK compliant adapters/couplers.
- Panels can be ordered configured.
- 25 Years System Warranty

